

TPU PLUS

ADBlue Stabiliser & Protection

Version 2 – SEPTEMBER 2019

WWW.MECATECH-PERFORMANCES.COM

DEFINITION

- ♦ **TPU Plus** is recommended for the treatment of AdBlue® in storage and distribution tanks as well as vehicles equipped with an SCR exhaust gas after treatment systems. (cars, trucks, buses, etc.)
- ♦ **TPU Plus** enables to make premium AdBlue® by adding the additive to a standard AdBlue® (Norm ISO22241 et DIN70070).
- ♦ **TPU Plus** stabilizes and improves the efficiency of AdBlue®.

ADVANTAGES

- ♦ **TPU Plus** reduces the AdBlue® surface tension for better atomization that ensures a better reaction of the catalytic converter (SCR). This in return reduces the NOx emissions and prevents pollution problems.
- ♦ **TPU Plus** is a preventive formulation of surfactants that prevents the crystallization of the urea and therefore protects the AdBlue® injectors and protects them from working poorly.
- ♦ The SCR system remains clean and efficient.

HOW TO USE

- ♦ **Add to the tank before filling up with AdBlue®**
- ♦ Squeeze the measuring bottle to obtain the correct amount in the upper reservoir (25mL).
- ♦ 25mL is sufficient for an ADBLue tank of 8 to 12 liters.
- ♦ Pour into the tank and fill it up with ADBLue.

SAFETY DATA

- ♦ Consult the SDS of the products available on our website www.mecatech-performances.com

PACKAGING

- ♦ Packaging: measuring bottle of 250mL for 25L of windshield washer liquid.
- ♦ **Art. #: MT045**

